GTI CMB-2028 ColorMatcher

- Color matching system with 5 different light sources for color evaluation.
- Simulated daylight D65, Storelight TL84, Home-light A, Officelight TL83, and UV.
- Light sources can be substituted per request.
- Painted in neutral Munsell N8 grey.
- Meets the requirements for the ASTM D1729 standard (including CIE Publication 51) for light quality, intensity, viewing symmetry, environ-mental conditions, and uniformity.
- Equipped with GTI's "ColorGuard II" digital lamp monitor, showing lamp hours used and when to relamp.

Daylight   Storelight   Homelight

- Programmable electronic light source sequencing, allowing for custom sequencing patterens using illuminated push buttons
- "Instant On" function, switch between light sources without dark warm-up pauses!
- Improved reflection lens technology for even light distribution.
- Minimal maintenance costs due to easy lamp re-placements
- Stable, hygienic steel construction
- Removable side walls to allow viewing of larger prints
- Optional height adjustable floorstand on casters
- Optional file drawers and shelves
- Accessories such as: 45° viewing stands (VS-45DC); VVT-1124 Viewing stand with ad-justable angle; and black panel insert set available.

CMB-2028/FS/2F-2028
CMB-2028 with optional adjustable
floor stand and 2 shelves

CMB-2028 with
color samples

CMB-2028 with
black panel
inserts

CMB-2028 with 45°
viewing stand VS-45DC

Details:

Illuminated Area:	71 cm wide x 51 cm deep x 48 cm tall
Outer Dimensions	76 cm wide x 55 cm deep x 63 cm tall (FS raises the height an extra 81—122 cm)
Shipping weight	32 kg (with FS + 25 kg)