

UnityColor Light2go Standard Light Station

Product no.: 43-10020

UnityColor Light2go II with standard light D65 (6500 K) or D50 (5000 K)

Mobile standard light luminaire for color matching, inspection and assessment

Finally there is a comfortable possibility to take the important standard light for color judgment with you. Standard light bulb UnityColor Light2go II makes it possible to illuminate objects of each size, places that are difficult to access, a surface of ca. 60 x 40 cm with standard light in order to make a concrete decision on color and finish quality. Light2go can also be used as a table lamp in the office and if needed it can easily be stowed in the working desk. Lightly it can be transported to the next place of action. Because of its high light intensity of 3500 Lux it can also be used outside (without solar radiation).

The light intensity increased 40% and the weight could be cuttett in half against the first generation.

Stationary glare-free and mobile working in the branches:

- painter and varnisher craftsman
- architects and construction experts, restructuring experts, consultants
- repairing branch: automotive painter, bulging doctor, leather repair
- vehicle inspector, experts, average adjuster
- model-making, clock repair
- dental laboratory for ink absorption on teeth and crowns
- furniture manufacturer (in production and repair service)
- eye doctors and company doctors for testing color button vision test or color vision test by means of pseudo isochromatic boards
- archaeology and in civil engineering (for layers of earth and rocks)
- print-/proof matching in agencies and printing shops (available with D50 and in set with 45° probe stand)

Technical data of Light2go II:

- standard light D65 (6500 Kelvin)
- equipped with 2 high value daylight bulbs
- color repeatability index > 95 at an even and spectral distribution
- power connection 230 V, 2 x 18 watt energy consumption
- ageing resistant , UV-transmissible micro pyramide stray disc and specially developed reflector
- desk size ca. 62 x 40 cm
- optimal lighted surface ca. 50 x 30 cm
- intensity of illumination > 3500 lux on the working desk
- distance from the desk to the lamp 30 cm
- hand lamp with handle 62 x 20 cm
- stable aluminium execution, all compmonents in high value powder coating neutral grey
- weight hand lamp 1,75 kg / gross weight only 6,15 kg, shipping weight 7,75 kg
- cable length ca. 5 m

Available in 4 versions:

- Light2go II with Daylight D65 for color control in industry
- Light2go II with Daylight D50 for color control in printing industry
- Light2go II with Striplight bicolor for surface control [... [more Info](#)]
- Light2go II with UV-Licht for optical brighteners, adhesives and primer

The standard light UnityColor Light2go II was developed from Torso-Verlag e.K. and is completely produced in Germany. You can test and visit this lamp in our exhibition room.

Options:

- Bundle: Light2go II without probe stand
- Bundle: Light2go II in bundle with 45° probe stand (+80,00 EUR)
- Light Sources: Light2go II /D65
- Light Sources: Light2go II /D50
- Light Sources: Light2go II with Strip Light bicolor (-15,00 EUR)
- Light Sources: Light2go II /UV (+40,00 EUR)

